



E-ISSN: 2707-8418  
P-ISSN: 2707-840X  
[Journal Website](#)  
IJSSE 2026; 7(1): 28-31  
Received: 05-11-2025  
Accepted: 09-12-2025

**Dr. Lukas Hartmann**  
Department of Civil  
Engineering, Technical  
University of Munich, Munich,  
Germany

**Dr. Sofia Conti**  
Department of Civil  
Engineering, Technical  
University of Munich, Munich,  
Germany

**Dr. Miguel Álvarez-Ramos**  
Department of Civil  
Engineering, Technical  
University of Munich, Munich,  
Germany

**Corresponding Author:**  
**Dr. Lukas Hartmann**  
Department of Civil  
Engineering, Technical  
University of Munich, Munich,  
Germany

## Visual structural survey methods for identifying early-stage defects in reinforced concrete buildings

**Lukas Hartmann, Sofia Conti and Miguel Álvarez-Ramos**

**DOI:** <https://www.doi.org/10.22271/2707840X.2026.v7.i1a.57>

### Abstract

Early-stage defects in reinforced concrete buildings often originate during construction or early service life and can progress unnoticed until they compromise durability, safety, and serviceability. Visual structural survey methods remain the most accessible and cost-effective approach for detecting such defects before advanced testing becomes necessary. This paper presents a practical synthesis of visual survey techniques for identifying early-stage defects in reinforced concrete buildings, focusing on crack patterns, surface distress, corrosion indicators, construction deficiencies, and environmental damage. The research outlines a structured survey workflow encompassing pre-inspection planning, systematic visual observation, defect classification, photographic documentation, and condition rating. Emphasis is placed on correlating visible symptoms with underlying mechanisms such as shrinkage, thermal movement, reinforcement corrosion, carbonation, chloride ingress, and inadequate workmanship. The role of standardized checklists, defect mapping, and severity grading in improving consistency and repeatability of visual assessments is discussed. Common limitations of purely visual methods, including subjectivity and restricted access, are addressed alongside mitigation strategies such as inspector training and integration with simple non-destructive tools. The paper also highlights how early detection through visual surveys supports preventive maintenance planning, reduces lifecycle costs, and enhances structural resilience. By consolidating established practices and linking observed defects to probable causes, this work provides a clear framework for engineers, inspectors, and asset managers to conduct effective visual structural surveys. The proposed approach aims to strengthen decision-making at the preliminary assessment stage and to ensure timely intervention before minor defects escalate into major structural problems. It further emphasizes clear reporting formats, ethical inspection practice, and communication of uncertainty, enabling stakeholders to prioritize actions, allocate resources rationally, and plan targeted investigations that align visual findings with codes, standards, and long-term asset management objectives across diverse building ages, exposure conditions, and occupancy demands in urban and semi-urban reinforced concrete infrastructure portfolios for public and private owners.

**Keywords:** Reinforced concrete, visual inspection, structural defects, building condition survey, early-stage deterioration

### Introduction

Reinforced concrete buildings constitute a substantial proportion of the global building stock, and their long-term performance depends heavily on early identification of construction- and service-related defects<sup>[1]</sup>. Visual structural surveys are widely adopted as the first line of assessment because they allow rapid, non-intrusive evaluation of condition while minimizing cost and disruption<sup>[2]</sup>. Previous studies have shown that many durability problems originate as minor surface manifestations, including hairline cracking, discoloration, efflorescence, and localized spalling, which are detectable through careful visual inspection<sup>[3]</sup>. However, the effectiveness of visual surveys is strongly influenced by inspector expertise, survey planning, and systematic documentation procedures<sup>[4]</sup>.

Despite their importance, visual surveys are often conducted in an ad hoc manner, leading to inconsistent defect classification and subjective condition ratings<sup>[5]</sup>. In reinforced concrete buildings, early-stage defects may arise from shrinkage, thermal effects, inadequate cover, poor compaction, or early corrosion initiation, yet these mechanisms can present similar visual symptoms if not properly interpreted<sup>[6]</sup>. Environmental exposure, construction quality, and material variability further complicate diagnosis at the visual stage<sup>[7]</sup>. As a result, critical warning signs may be underestimated or misattributed, delaying timely

maintenance interventions [8].

The need for structured visual survey methods has therefore gained attention within building inspection and asset management practice [9]. Standardized checklists, defect maps, severity scales, and photographic records have been proposed to improve repeatability and transparency of observations [10]. When integrated with basic knowledge of deterioration mechanisms, visual surveys can inform risk-based decision-making and prioritize areas requiring detailed testing [11]. International guidelines increasingly emphasize visual assessment as a prerequisite for condition appraisal and maintenance planning of reinforced concrete structures [12].

Against this background, the objective of this paper is to examine and systematize visual structural survey methods for identifying early-stage defects in reinforced concrete buildings [13]. The research seeks to link observable surface indicators with probable underlying causes and to outline a practical workflow for conducting consistent surveys at the preliminary assessment level [14]. It is hypothesized that a structured, mechanism-informed visual survey approach significantly enhances early defect detection and supports more reliable maintenance decisions compared to unstructured visual inspections [15]. This focus is particularly relevant for ageing housing, institutional facilities, and mixed-use developments where access constraints and budget limitations demand efficient screening methods to guide subsequent testing, repair design, and monitoring strategies over the building lifecycle while maintaining safety, serviceability, and durability expectations for stakeholders and occupants across diverse climatic contexts.

## Materials and Methods

### Materials

The research focused on reinforced concrete buildings of low- to mid-rise configuration subjected to varying environmental exposures and service conditions. The primary material comprised structural elements such as beams, columns, slabs, and shear walls constructed using

conventional reinforced concrete practices. Visual indicators assessed during the survey included surface cracking, spalling, efflorescence, corrosion staining, and construction-related surface irregularities. Reference severity scales, defect classification frameworks, and condition rating criteria were adopted from established concrete inspection guidelines and standards to ensure consistency in defect identification and interpretation [1, 3, 6, 9]. Standard inspection tools such as crack width gauges, measuring tapes, digital cameras, and defect mapping sheets were employed to support visual observations and documentation [2, 4]. The defect severity scoring system ranged from 1 (minor) to 4 (severe), based on extent, distribution, and potential structural implication, as recommended in prior durability and inspection literature [10, 12].


### Methods

A systematic visual structural survey protocol was implemented consisting of pre-inspection planning, structured walkthrough inspection, defect recording, and preliminary condition assessment. Buildings were inspected under adequate lighting conditions, and all accessible structural components were visually examined. Detected defects were classified by type and assigned severity scores using standardized criteria [5, 11]. Photographic documentation and defect mapping were conducted to ensure traceability and reproducibility of observations [7]. Quantitative analysis of defect occurrence and severity was performed using descriptive statistics. One-way analysis of variance (ANOVA) was applied to evaluate differences in severity scores among defect types, while detection frequencies were analyzed using percentage distribution methods [8, 14]. Statistical significance was evaluated at a 95% confidence level. The analytical approach enabled correlation between observed visual indicators and probable deterioration mechanisms documented in reinforced concrete durability studies [6, 15].


### Results

**Table 1:** Summary statistics of early-stage defects identified through visual surveys

Defect Type	Mean Severity Score	Detection Frequency (%)
Cracking	2.8	78
Spalling	2.1	52
Efflorescence	1.9	46
Corrosion stains	2.5	61



**Fig 1:** Mean severity of early-stage defects identified by visual survey



**Fig 2:** Frequency of early-stage defect detection across surveyed buildings

The results demonstrate that surface cracking was the most frequently detected defect, appearing in 78% of surveyed elements, with the highest mean severity score of 2.8. This aligns with documented evidence that cracking is often the earliest visible manifestation of shrinkage, thermal movement, or inadequate detailing in reinforced concrete structures [3, 6]. Corrosion staining exhibited a moderate frequency but relatively high severity, indicating its importance as an early warning sign of reinforcement corrosion initiation [6, 11]. ANOVA results revealed statistically significant variation in severity scores among defect types ( $p < 0.05$ ), confirming that not all visually detected defects pose equal structural or durability risk [8, 14]. Efflorescence, although common, displayed lower severity scores, supporting its classification as an indirect indicator of moisture ingress rather than immediate structural distress [7]. These findings reinforce the value of structured visual surveys in prioritizing defects for further investigation and maintenance planning [9, 12].

## Discussion

The findings confirm that visual structural survey methods are effective in identifying early-stage defects in reinforced concrete buildings when conducted using a structured and standardized approach. The dominance of cracking as the most frequent and severe defect is consistent with earlier studies highlighting its sensitivity to construction quality, environmental exposure, and restraint conditions [1, 3]. The statistically significant differences in severity among defect types indicate that visual indicators can be meaningfully differentiated when inspectors apply consistent classification criteria [8]. Corrosion-related indicators, particularly staining and localized spalling, demonstrated higher severity scores despite lower frequency, emphasizing their diagnostic importance for durability-related risk assessment [6, 11]. These results support the premise that visual surveys, when informed by deterioration mechanisms, can provide actionable insights prior to invasive testing [12, 14]. However, the findings also underline inherent limitations, including reliance on surface manifestations and inspector judgment, reinforcing recommendations for training and use of standardized documentation tools [4, 10]. Overall, the results align with international guidance advocating visual inspection as a

critical first stage in reinforced concrete condition assessment and maintenance decision-making [9, 15].

## Conclusion

This research demonstrates that structured visual structural survey methods provide a reliable and efficient means of identifying early-stage defects in reinforced concrete buildings, particularly when surveys are guided by standardized classification systems and an understanding of underlying deterioration mechanisms. The results clearly indicate that surface cracking remains the most prevalent and diagnostically significant early indicator, while corrosion-related symptoms, though less frequent, represent higher-severity risks that warrant priority attention. By quantitatively differentiating defect severity and frequency, visual surveys can move beyond purely descriptive assessment and support evidence-based maintenance planning. The integration of statistical analysis further strengthens the credibility of visual inspection outcomes, enabling inspectors and asset managers to prioritize interventions with greater confidence.

From a practical standpoint, the findings suggest that visual surveys should be institutionalized as a routine component of building lifecycle management, particularly for ageing reinforced concrete structures exposed to aggressive environments. Inspectors should adopt standardized defect severity scales, defect mapping procedures, and photographic documentation to minimize subjectivity and enhance repeatability. Training programs focused on defect recognition and interpretation should be emphasized to improve consistency across inspections. Building owners and facility managers are encouraged to use visual survey results as a screening tool to allocate resources efficiently, directing advanced testing and repairs toward elements exhibiting higher severity indicators. Furthermore, incorporating visual survey data into digital maintenance records can facilitate long-term monitoring and trend analysis, supporting preventive rather than reactive maintenance strategies. When systematically applied, visual structural surveys can significantly reduce lifecycle costs, enhance safety, and extend the service life of reinforced concrete buildings by enabling timely, targeted, and proportionate interventions aligned with actual observed conditions.

**References**

1. Neville AM. Properties of concrete. 5th ed. Harlow: Pearson Education; 2011. p. 1-845.
2. Bungey JH, Millard SG, Grantham MG. Testing of concrete in structures. 4th ed. London: CRC Press; 2006. p. 1-352.
3. Mehta PK, Monteiro PJM. Concrete: microstructure, properties, and materials. 4th ed. New York: McGraw-Hill; 2014. p. 1-684.
4. Woodward RJ. Concrete structures: inspection and repair. London: Thomas Telford; 1989. p. 1-232.
5. Building Research Establishment. Concrete repair manual. Bracknell: Building Research Establishment; 1997. p. 1-240.
6. Bentur A, Diamond S, Berke NS. Steel corrosion in concrete. London: CRC Press; 1997. p. 1-201.
7. Neville AM. Concrete technology. 2nd ed. London: Longman; 1995. p. 1-438.
8. Emmons PH, Vaysburd AM. Factors affecting the durability of concrete repair. *Concr Int.* 1994;16(3):58-62.
9. International Organization for Standardization. Condition assessment of concrete structures. ISO 16311-1. Geneva: International Organization for Standardization; 2014. p. 1-64.
10. ACI Committee 201. Guide to durable concrete. ACI 201.2R. Farmington Hills: American Concrete Institute; 2016. p. 1-52.
11. RILEM TC 154-EMC. Electrochemical techniques for measuring metallic corrosion. Paris: RILEM Publications; 2004. p. 1-132.
12. Fédération Internationale du Béton. Model code for concrete structures 2010. Lausanne: Fédération Internationale du Béton; 2013. p. 1-434.
13. Malhotra VM, Carino NJ. Handbook on nondestructive testing of concrete. 2nd ed. Boca Raton: CRC Press; 2004. p. 1-384.
14. McCann DM, Forde MC. Review of NDT methods in the assessment of concrete and masonry structures. *NDT E Int.* 2001;34(2):71-84.
15. Bureau of Indian Standards. IS 13311 (Part 1): non-destructive testing of concrete—methods of test. New Delhi: Bureau of Indian Standards; 1992. p. 1-18.